

Type	OD (mm)	ODmin ODmax (mm)	Nominal Pressure PN	a (mm)	b (mm)	Cmax with steel band insert (mm)	d ~ (mm)	H ~ (mm)	Bolt (mm)	Approx. Weight (kg/piece)
REP 2)	35	34.5 - 35.5	16	62.4	14.4	8	55	75	M8	0.5
	38	35.6 - 38.5	16	62.4	14.4	8	60	80	M8	0.5
	42.4	41.7-42.9	16	62.4	14.4	8	65	85	M8	0.6
	44.5	44.0 - 45.0	16	62.4	14.4	8	65	85	M8	0.6
	48.3	45.5 - 48.8	16	62.4	14.4	8	70	90	M8	0.6
	54	53.6 - 54.9	16	77.4	29.4	17	75	95	M8	0.8
	57	56.3 - 57.6	16	77.4	29.4	17	80	100	M8	0.8
	60.3	59.5 - 60.9	16	77.4	29.4	17	80	100	M8	0.8
	73	72.6 - 74.0	16	98	40.3	25	95	115	M 10	1.4
	76.1	75.2 - 76.9	16	98	40.3	25	100	120	M8	1.4
	84	83.0 - 85.0	16	98	40.3	25	105	125	M8	1.5
	88.9	88.0 - 89.8	16	98	40.3	25	110	130	M8	1.5
	101.6	101.0-102.9	16	98	40.3	25	125	145	M10	1.6
	104	103.0-106.0	16	98	40.3	25	125	145	M8	1.6
	108	106.0-109.1	16	98	40.3	25	130	150	M8	1.7
	110	109.0-111.0	16	98	40.3	25	130	150	M8	1.7
	114.3	113.0-115.4	16	98	40.3	25	135	155	M8	1.7
	118	116.6-119.2	16	98	40.3	25	140	160	M10	1.7
	129	128.0-131.0	16	113	50	35	155	185	M10	2.4
	133	131.0-134.3	16	113	50	35	160	190	M10	2.4
	139.7	138.0-141.1	16	113	50	35	165	195	M10	2.5
	141.6	139.6-142.0	16	115	50	35	170	200	M12	2.5
	144	142.4-145.5	16	113	50	35	170	200	M12	2.5
	154	153.0-156.0	16	113	50	35	180	210	M10	2.6
	159	157.0-160.8	16	113	50	35	185	215	M10	2.7
	168.3	166.0-170.0	16	113	50	35	195	225	M10	2.8
	170	168.2-171.9	16	113	50	35	195	225	M12	2.8

Type	rw (mm)	ODmin ODmax (mm)	M.A.W.P. 1) (bar)	a (mm)	b (mm)	Cmax with steel band insert (mm)	d ~ (mm)	H ~ (mm)	Bolt (mm)	Approx. Weight (kg/piece)
			REP	REP						REP
2) REP	206	202,0 - 208,0	13.7	139	74	35	240	270	M12	3.8
	219.1	216,0-221,0	13.7	139	74	35	250	280	M12	3.9
	254	250,0 - 256,0	12	139	74	35	285	315	M12	4.3
	267	264,0 - 269,0	12	139	74	35	300	330	M12	4.5
	273	270,0 - 275,0	12	139	74	35	305	335	M12	4.6
	306	302,0 - 308,0	9	139	74	35	335	370	M 12	4.8
	323.9	320,0 - 327,0	9	139	74	35	355	385	M12	5.1
	355.6	352,0 - 359,0	9	139	74	35	385	420	M12	5.2
	406.4	402,0-410,0	7.5	139	74	35	435	470	M12	5.8
	508	505,0-510,0	5.5	139	74	35	540	570	M12	7.2
	609.6	606,0-613,0	4.5	139	74	35	630	670	M12	8.2
	711.2	707,0-715,0	4	139	74	35	740	775	M12	8.9
	812.8	808,0-817,0	3.2	139	74	35	845	875	M12	9.9
	1219.2	1216,0-1222,0	2	139	74	35	1250	1280	M12	13.6